

Green Star

Daylight Hand Calculation Guide

16th September 2013

Changelog

Date	Version	Change
16 th Sept 2013	0.1	Draft Issued for Comment



Contents

Content	S	2	
1.0	Introduction	3	
2.0	Overshadowing Requirements	4	
3.0	Visual Transmittance of Glazing	5	
4.0	Calculating the Zone of Compliance	6	
5.0	Documentation Guidelines	8	
6.0	References	8	
Append	Appendix A		



1.0 Introduction

The hand calculation method for daylight outlined in this guide is applicable to the following Green Star rating tools:

- Green Star Office v3;
- Green Star Education v1 (first 3 points only), and
- Green Star Public Building v1.

For the rating tools listed above compliance is demonstrated by calculating the percentage of the nominated area which has a Daylight Factor of 2% or greater, the hand calculation as detailed in section 4.0 of this guide is deemed acceptable to identify a zone of compliance from which the percentage of nominated area that is compliant can be calculated.

Green Star – Office Interiors v1.1

For the Green Star Office Interiors v1.1 rating tool compliance is demonstrated by identifying the percentage of work settings located in an area of the floor plate that has a daylight factor of 2.5% or greater as measured at finished floor level, the hand calculation as detailed in section 4.0 of this guide is deemed acceptable to identify a zone of compliance. Any worksettings that are located within the zone of compliance are deemed to comply.

Project registered under Green Star rating tools not covered by this guide are required to submit a credit interpretation request detailing how the guide is being applied to their project.

This document is being provided as a draft for comment. GBCA encourages project teams to use this guide to claim points instead of modelling. In addition, GBCA invites people to provide feedback on the guidance stated below.

How to demonstrate compliance

To use the hand calculation method the project must meet the following requirements:

- The project is not overshadowed, in accordance with the overshadowing requirements outlined in section 2.0 of this guide; and
- The glazing has a visual light transmittance (VLT) of equal to or greater than 40% as outline in section 3.0 of this guide.

It should be noted that for an Education v1 submission this method cannot be used to demonstrate compliance with the additional point.

The foundation for this method of hand calculation is taken from the DETR Good Practice Guide 245, Desktop guide to daylighting - for architects.



2.0 Overshadowing Requirements

Projects where external shading does not impinge on the direct 25 degree line from the mid-height (centre) of the window are deemed to not be overshadowed. External shading includes: buildings, cliffs, and any other solid structure. External shading does not include trees. Please refer to Figure 1 below for further guidance.







3.0 Visual Transmittance of Glazing

This hand calculation method assumes that there is no significant loss of light due to external obstructions, tinted glazing or interior screening.

For this hand calculation method the glazing must have a visible light transmittance equal to or greater than 40%.

The following is an indication of typical VLT values for various glazing types:

Glazing Type	VLT Range
Clear single glazing	~70 - 90%
Tinted single glazing (green)	~70%
Tinted single glazing (grey)	~20%
Clear double glazing	~70 - 80%
Double glazing with a low emissivity coating	~40 - 70% (but can be as low as 10%)

NB: dirt can give a further 5% reduction in VLT with normal cleaning in an urban setting. Reductions in VLT due to dirt do not need to be included for the purposes of a Green Star Daylight assessment.



4.0 Calculating the Zone of Compliance

The zone of compliance is an area (in the horizontal plane) that is the width of the window by a depth which is twice the height of the window head above desktop/table top level as illustrated in the Figure 2 below.

Depth of the Zone of Compliance $= h \times 2$ 'w'width of the Zone of Compliance = Width of the glazing Zone of Complance $= h \times 2 \times w$

Additional Notes:

- When plotting the depth of the Zone of Compliance the zone may not be drawn past solid or glazed partitions.
- Any column or mullion < 0.5m in width can be disregarded and the glazing can be considered to be continuous in width.
- For the purposes of this hand calculation desktop/table top level is set at 700mm AFFL for all rating tools.

Figure 2: Dimensions for calculating the zone of compliance.





When determining the dimension for 'h' the following applies (see the Figure 3 below for further guidance):

- 'h' is the height of the window head above desktop/table top level (700mm) (Diagram A)
- If the bottom sill of the glazing is above desktop/table top level (700mm) the dimension for 'h' is taken from the bottom sill of the • glazing (Diagram B).

Figure 3: How to determine the dimension for 'h'.



Once the area of the zone of compliance has been calculated the percentage of compliant nominated area can be calculated.



5.0 Documentation Guidelines

Where this hand calculation methodology is being used, please nominate this on the cover page and refer to the documentation requirements outlined here. The documentation outlined here is to be provided in lieu of the documentation outlined within the Technical Manual.

Documentation Guidelines - Deemed to Satisfy for Design and As Built

Submit all the evidence and ensure it readily confirms compliance.

□ Short report

Drawings and plans must be Tender or As Built in line with the rating being sought.

□ Floor Plans

□ Façade Drawings

□ Site Plan

For a Design Submission

□ Extract(s) from the Specification(s)

For an As Built Submission

□ Confirmation from the Head Contractor

Short report prepared by a suitably qualified professional that describes how the Credit Criteria have been met using the hand calculation method for Deemed to Satisfy and referencing the supporting drawings. The short report must:

- Identify all spaces within the building;
- Nominate the spaces where the Credit Criteria has been met, and their area; and
- Provide a summary table to demonstrate that compliant spaces jointly account for the stipulated proportion of the NLA.

Floor Plans clearly identifying those areas deemed to satisfy using the hand calculation method. All measurements and areas for the calculation must be shown on the plan.

Façade Drawings identifying the façade materials in the design and indicating the dimention for 'h' in the hand calculation.

Site Plan extrending to the surrounding area, identifying the heights and location of any surrounding buildings

Extract(s) from the Specification(s) where all glazing properties and minimum visual transmittance levels are nominated.

Confirmation from the Head Contractor that the specified glazing products or an equivalent were installed in the building.

6.0 References

• The Department of Environment, Transport and the Regions (DETR),1998, Good Practice Guide 245 'Desktop guide to daylighting – for Architects', <u>http://www.cibse.org/pdfs/GPG245.pdf</u>



Appendix A

Please note that the plans in this appendix are provided as an example of how the daylight hand calculation is applied, and can be illustrated. It is not an example of illustrating compliance or non-compliance.





01 PERIMETER BLIND ELEVATION - WEST FACADE 1:100



Calculating the Zone of Compliance. Depth of the Zone of Compliance = $h \ge 2 = 4 m$. 'w' width of the Zone of compliance = width of glazing^{*} Zone of Compliance = $h \ge 2 \ge W$ *'

The zone of compliance may not be drawn past solid or glazed partitions.

Any column or nullion < 0.5m in width can be disregarded and the glazing is treated as continuous.

AS BUILT

Cad\ Active\piot\CD-J-02 Perimeter Bind Elevetion.don

BN/N

BlighVollerNieldArchitecture

Telephone +61 3 9639 9199 Facsimile +61 3 9639 9188 www.bvn.com.au

INTELLECTUAL PROPERTY © COPYRIGHT BLIGH VOLLER NIELD PTY LT AGREED IN WRITING: ALL RIGHTS TO USE T TO PHYMENT IN FULL OF ALL BVN CHARGES ISSUE DATE FOR 09.11.07 FOR CONSTRUCTION CONSULTANT DAVIS LANGDON tel 02 9956 8822 fax 02 9956 8848 CONSULTANT LINCOLNE SCOTT

tel 02 8907 0900 fax 02 9957 4127 CLIENT

GBCA L15, 179 ELIZABETH STREET SYDNEY NSW 2000 CLIENT PROJECT No.

PROJECT

GREEN BUILDING COUNCIL OF AUSTRALIA

BVN PROJECT NUMBER

M0709010

TRUE NORTH

GRAPHIC SCALE 5000

SCALE

1:100 at A2 STATUS

DO NOT SCALE

PROJECT NORTH

()

FOR CONSTRUCTION DRAWING

PERIMETER BLIND ELEVATION PLAN		
DRAWING NUMBER	ISSU	
A-J-02	A	

ISSUE



IEQ-4: 1

I COPYRIG AGREED IN V TO PAYMENT BE USED FO CREATED AN DOCUMENT USE OF THIS LIMITING BM AND AGAINS	HT BUGH VOLLERI MRITING: ALL RIGH IN FULL OF ALL BI R THE DOPRESS PL ID DELIVERED, AS MAY NOT BE OTHE ID DOCUMENT IS AT IN'S RIGHTS THE UL IT ALL LOSS SO AP	NED PTV IDT (SMM) UNLESS OTHERWISE INT OVIET HIS DOCUMENT AND SUBJECT INT OHARTES DOCUMENT AND SUBJECT INT OHARTES INT OF A DOCUMENT AND CALL PROGE AND PTV OLITET TOR WHOM THIS INTELED IN WITHOUT OF ISSUE INTELE USERS AND INTELLATION OF A DOCUMENT THE USERS AND INTELLATION OF A DOCUMENT SING.
ISSUE	DATE	FOR
A	09.11.07	FOR CONSTRUCTION
CONSUL DAVIS tel 02 CONSUL	TANT S LANGE 9956 882 TANT	DON 22 fax 02 9956 8848
LINCO OBI 02	8907 090	00 fax 02 9957 4127
LINCO tel 02 CLIENT GBCA L15, 1 SYDN CLIENT I	79 ELIZA EY NSI	ABETH STREET W 2000
LINCO tel 02 CLIENT GBCA L15, 1 SYDN CLIENT I	79 ELIZ/ EY NSI PROJECT NO	ABETH STREET W 2000
CLIENT GBCA L15, 1 SYDN CLIENT I PROJEC	79 ELIZJ EY NSI PROJECT NO N BUILD JSTRALI	ABETH STREET W 2000
LINCC tel 02 CLIENT GBCA L15, 1 SYDN CLIENT I PROJEC GREE OF AL OF AL	T N BUILD JSTRALI	ABETH STREET N 2000 DING COUNCIL A BER
LINCC tel 02 GBCA L15, 1 SYDN CLIENT I PROJEC GREE DF AL SVN PRC	T N BUILD JSTRALI	ABETH STREET W 2000 2. DING COUNCIL A BER
LINCC tel 02 CLIENT GBCA L15, 1 SYDN CLIENT I SYDN CLIENT I SYDN SYDN SYDN SYDN SYDN SYDN SYDN SYDN	T N BUILD JSTRALI JJET NUME 2010 RTH	ABETH STREET V 2000 DING COUNCIL A SER PROJECT NORTH
LINCC tel 02 CLIENT GBCA L15, 1 SYDN CLIENT I PROJEC GREE DF AL 3VN PRO GREE DF AL 3VN PRO GREE DF AL 3VN PRO GRAPHIC	T IN BUILD JSTRALI JSTRALI SCALE 200	200 fax 02 9957 4127 ABETH STREET W 2000 2. DING COUNCIL A SER PROJECT NORTH 00 5000
LINCC tel 02 CLIENT GBCA L15, 1 SYDN CLIENT I PROJEC GREE DF AL SYN PROJEC OF AL SYN PROJEC OF AL SYN PROJEC OF AL SYN PROJEC	T IN BUILD JSTRALI DUCT NUME DOT10 INTH ISSCALE 200	ABETH STREET W 2000 DING COUNCIL ABER PROJECT NORTH PROJECT NORTH 5000

PERIMETER BLIND PLAN

ISSUE
Α

BrisbaneMelbourneSydneyLevel 2,Level 17Level 1579 Adelaide St500 Collins St179 Elizabeth StBrisbane QLD 4000Melbourne VIC 3000Sydney NSW 2000T / 07 3229 3299T / 03 8612 2000T / 02 8239 6200